



PROFLEX[®] M42 / PROFLEX[®] SW M42

THE PERFECT BAND SAW BLADE FOR PROFILES




NEW!

- durable and resistant
- less finishing thanks to low-burr cutting edges

PROFLEX® M42 / PROFLEX® SW M42 

The perfect band saw blade for profiles



WIKUS continues to sharpen its profile with the new PROFLEX® M42 bimetal band saw blade for processing profiles and girders. Thanks to the special profile tooth and also the extended connection of cutting material and carrier band, the PROFLEX® M42 is extremely sturdy.

The innovative production procedure not only extends the service life of the carrier band, it also reduces the risk of a broken band. The superfinishing on the cutting edge of the teeth and the chip space enhances performance, reduces noise emission and the formation of burr, and also improves the cutting surface.

ADVANTAGES AT A GLANCE

resistant to broken teeth
thanks to extremely sturdy tooth contour



less finishing
thanks to low-burr cutting edges



less susceptible to vibration
thanks to special tooth form



less broken bands
thanks to new production procedure




low noise emission
thanks to variable tooth pitch and positive rake angle

APPLICATION

- profiles and girders, for metal and steel construction
- optimal for cutting with interrupted cutting channel

FEATURES

- extremely sturdy tooth contour
- variable tooth pitch
- specific step set
- M42 tooth edge with positive rake angle

**Profile tooth**

PROFLEX® M42

Dimensions Width x Thickness mm Inch		Tooth pitch in tpi					
		12-16	8-11	5-7	4-6	3-4	2-3
20 x 0,90	3/4 x 0,035	P	P	P			
27 x 0,90	1-1/16 x 0,035	P	P	P	P		
34 x 1,10	1-3/8 x 0,042		P	P	P	P	
41 x 1,30	1-5/8 x 0,050		P	P	P	P	P
54 x 1,30	2-1/8 x 0,050			P	P	P	P
54 x 1,60	2-1/8 x 0,063			P	P	P	P
67 x 1,60	2-5/8 x 0,063					P	P
Contact length (mm)		< 20	10-50	40-70	50-90	80-160	150-310

PROFLEX® SW M42

Special design for profiles made of residual stress material

like PROFLEX® M42, plus:

- Advantages:**
 - no jamming in the cutting channel
- Application:**
 - profiles and girders with residual stress
- Features:**
 - extra wide step set

Dimensions Width x Thickness mm Inch		Tooth pitch in tpi					
		12-16	8-11	5-7	4-6	3-4	2-3
34 x 1,10	1-3/8 x 0,042					P	P
41 x 1,30	1-5/8 x 0,050					P	P
54 x 1,30	2-1/8 x 0,050					P	
54 x 1,60	2-1/8 x 0,063					P	P
67 x 1,60	2-5/8 x 0,063					P	P
Contact length (mm)		< 20	10-50	40-70	50-90	80-160	150-310

The [current availabilities](#) of the new PROFLEX® M42 are [highlighted in colour](#), data as at, 26st November 2018. All the other dimensions will gradually be changed to the optimised version.

New: QR code for ParaMaster® APP

When scanning the QR code on the blade with the ParaMaster® APP, the blade data are transmitted automatically.

P = Profile tooth, Photo below: PROFLEX® M42





**NEW:
ParaMaster® APP**



**WIKUS-Sägenfabrik
Wilhelm H. Kullmann GmbH & Co. KG**

Melsunger Str. 30
34286 Spangenberg, Germany

Phone: +49 5663 500-0
Fax: +49 5663 500-57

www.wikus.com
info@wikus.com



© WIKUS-Sägenfabrik.

All rights reserved. Not to be reproduced in part or in whole. No responsibility is taken for the accuracy of this information. Despite the fact that WIKUS takes great care in assembling and constantly reviewing its data, the company assumes no liability or guarantees for the completeness, correctness or up to datedness of the information provided. Pictures may differ from the original. The product range may change after the brochure has been printed. The trademarks designated with the "®" are registered trademarks by WIKUS-Sägenfabrik Wilhelm H. Kullmann GmbH & Co. KG unless otherwise indicated. These trademarks are protected in Germany, the European Union and many other countries worldwide. Printed in Germany. 2018-12-05

Innovative precision tools
designed and manufactured
in Spangenberg, Germany

